

LOW LEVEL MINIFOLD UNIT



Minifold Unit

The Minifold Unit is ideal for all the jobs around the home that requires a steady hand, such as painting windows frames, hanging wallpaper, cleaning the gutters, or just trimming the hedge.

Either inside or outside your home, the Minifold Unit is easy to assemble and ready to use in minutes.

- Ideal for one man use, unfold the unit, fit the board and start work.
- Easily portable and manoeuvrable, either open or closed, the unit passes easily through standard doorways.
- Both lightweight and robust.
- Provides a working platform 0.7m wide and 1.5m long.
- Six optional platform levels between 0.2m and 1.7m will suit most requirements.
- Fitted with lockable 5" castors and non-slip platform boards.
- Captive folding bracing system means minimum components.
- When closed the board will hook onto the unit for compact storage.
- Easily transportable, compact when folded flat to fit in a small van, estate car or on a roof rack.

Optional Extra's Include

- Guardrail Pack – high level safety
- Adjustable Legs and Castors – for uneven ground
- Extension packs to generate platform levels of 3m, 3.6 and 5.5m.

MKTOWER SERVICES LTD

HIRE – SALES – REPAIRS - TRAINING

Tel: 0844 884 5191 | www.mktowerservices.com

Address: Unit 6A Pineham Farm – Haversham - Milton Keynes- MK19 7DP | Ben@MKTower.com

LOW LEVEL MINIFOLD UNIT

Minifold Unit

Assembly Instructions

Ensure all parts are present and are not damaged before assembling

Minifold Basic Unit

Comprising of...

- 4 x K548 - Castors with adaptors
- 1 x MFFU - Minifold Base unit
- 1 x MFPT - Minifold Trapdoor platform

1. Ensure that all castors are firmly fitted to the folding frame by tightening the bolt located directly under the castor housing.
2. Open folding frame and engage toggle clamps.
3. Position platform on a rung at desired level.
4. Always gain access to the platform via the trapdoor, when appropriate.



	Minifold Unit
Platform Height	0.2m – 1.7m
Safe Working Load	150Kg
Dimensions	0.7m Width x 1.5m Length

General Safety Rules:

1. Do not use on unstable ground such as loose bricks, boxes or blocks.
2. Remove all personnel and materials before moving the unit.
3. When moving the unit, apply force manually by pushing at the base.
4. Do not gain extra height by using boxes, ladders, on the platform.
5. Ensure that the castors are locked before use.
6. Do not overload the unit.
7. Do not overreach out of the unit.

Minifold Guardrail Set

Comprising of...

- 2 x MFGR - Guardrail frames
- 4 x TTHB - 1.5m Horizontal braces

1. Fit the guardrail frame to folding frame
2. Engage interlock clips
3. Fit four horizontal braces to vertical members of the frames. Hooks must face outwards on the vertical.



Minifold Toeboard Set

Comprising of...

- 1 x SWTB - 1.5m x SW Toeboard Assembly

1. Fit the toeboards around the platform as illustrated to create a barrier around the foot area.



MAX SAFE WORKING LOAD FOR PLATFORM / STRUCTURE

150KG

For more information on this unit or the Minifold Extension packs, please contact us

Tel: 0844 884 5191 | www.mktowerservices.com

Address: Unit 6A Pineham Farm – Haversham - Milton Keynes- MK19 7DP | Ben@MKTower.com